

List of Figures

Figures		Page
3.1	Degree of hydration of the mineral components in cement (%)	14
3.2	Degree of pozzolanic reaction (%)	15
4.1	Relationship between s/a (by volume) and void content	20
4.2	Concrete specimens in the city-sheltered conditions	23
4.3	Example of carbonated concrete specimens after being tested	24
4.4	Example of carbonated mortar specimens after being tested	25
4.5	Accelerated carbonation chamber	25
4.6	Example of mortar specimens after being spitted	28
5.1	Carbonation depth of fly ash concrete exposed for 12 months ($\gamma = 1.2$)	33
5.2	Carbonation depth of fly ash concrete exposed for 12 months ($\gamma = 1.4$)	33
5.3	Carbonation depth of fly ash concrete exposed for 24 months ($\gamma = 1.2$)	33
5.4	Carbonation depth of fly ash concrete exposed for 24 months ($\gamma = 1.4$)	34
5.5	Carbonation coefficient of fly ash concrete ($\gamma = 1.2$)	34
5.6	Carbonation coefficient of fly ash concrete ($\gamma = 1.4$)	34
5.7	Total permeable void of mortar (at age of 28 days)	35
5.8	Total CH in mortar (cured and carbonated for 28 days)	35
5.9	Carbonation depth of fly ash mortar exposed for 12 months ($\gamma = 1.2$)	35
5.10	Carbonation depth of fly ash mortar exposed for 12 months ($\gamma = 1.4$)	36
5.11	Carbonation depth of fly ash mortar exposed for 24 months ($\gamma = 1.2$)	36
5.12	Carbonation depth of fly ash mortar exposed for 24 months ($\gamma = 1.4$)	36
5.13	Carbonation coefficient of fly ash mortar ($\gamma = 1.2$)	37
5.14	Carbonation coefficient of fly ash mortar ($\gamma = 1.4$)	37
5.15	Carbonation coefficient of fly ash concrete (w/b = 0.5, FA1)	38
5.16	Carbonation coefficient of fly ash concrete (w/b = 0.6, FA1)	38
5.17	Carbonation coefficient of fly ash mortar (w/b = 0.5, FA1)	38
5.18	Carbonation coefficient of sheltered fly ash concrete ($\gamma = 1.2$, FA1)	39
5.19	Carbonation coefficient of sheltered fly ash concrete ($\gamma = 1.2$, FA1)	39

5.20	Carbonation coefficient of sheltered fly ash concrete ($\gamma = 1.4$, FA1)	39
5.21	Carbonation coefficient and 28-day compressive strength (city-sheltered)	40
5.22	Carbonation coefficient and 28-day compressive strength (city-non-sheltered)	40
5.23	Carbonation coefficient and 28-day compressive strength (rural)	41
5.24	Carbonation coefficient and 28-day compressive strength (seaside)	41
5.25	Carbonation depth and compressive strength (10% fly ash replacement)	42
5.26	Carbonation depth and compressive strength (30% fly ash replacement)	42
5.27	Carbonation depth and compressive strength (50% fly ash replacement)	42
5.28	Carbonation coefficient of concrete and mortar ($\gamma = 1.2$)	43
5.29	Carbonation coefficient of concrete and mortar ($\gamma = 1.4$)	43
5.30	Carbonation depths of concrete specimens tested in natural (city-sheltered) and accelerated environments	44
5.31	Carbonation depths of concrete specimens tested in natural (city-non-sheltered) and accelerated environments	45
5.32	Carbonation depths of concrete specimens tested in natural (rural) and accelerated environments	45
5.33	Carbonation depths of concrete specimens tested in natural (seaside) and accelerated environments	45
5.34	Verification of the city-sheltered environment	47
5.35	Verification of the city-non-sheltered environment	47
5.36	Verification of the rural environment	48
5.37	Verification of the seaside environment	48
5.38	Carbonation depth (1 month exposure) and water-curing period	49
5.39	Carbonation depth (2 months exposure) and water-curing period	50
5.40	Effect of environmental relative humidity on carbonation depths of mortars	51
5.41	Effect of environmental temperature on carbonation depth of mortars	52
5.42	Carbonation depth and 28-day compressive strength of mortar	53
5.43	Carbonation depth and the corresponding compressive strength of mortar	54
5.44	Fraction number of the specimen for relative water content test	55
5.45	Relative water content distribution (C_w) in mortars	56
5.46	Relative water content distribution (C_w) in cement only mortars	57
5.47	Relative water content distribution (C_w) in mortars and no-sand concrete	57

5.48	Relative water content distribution in-pastes	58
6.1	Flow chart of the model for simulating corrosion of reinforcing steel due to carbonation	59
6.2	Relationship between relative humidity and relative water content in concrete	61
6.3	Diagram for showing the flux of water movement in concrete	62
6.4	Weight ratio of free water per total binder of cement-only mixtures	62
6.5	Weight ratio of free water per total binder of cement-fly ash mortar (w/b = 0.5)	62
6.6	Average pore diameter of paste (w/b = 0.4)	63
6.7	Total porosity of cement-only paste	64
6.8	Relative water content in mortar (cured and dried for 28 days)	65
6.9	Relative water content in paste (cured and dried for 28 days)	66
6.10	Relative water content in no-sand concrete (w/b = 0.4, cured and drying for 28 days)	67
6.11	CH in mortar specimen (Papadakis's data): w/b = 0.5 and A/B = 3.0	72
6.12	CH in mortar specimen (authors' data) at 28 days (paste volume = 0.50 m ³)	72
6.13	Carbonation depth of concrete tested in city-sheltered environment	73
6.14	Carbonation depth of concrete tested in city-non-sheltered environment	74
6.15	Carbonation depth of concrete tested in rural environment	75
6.16	Carbonation depth of concrete tested in seaside environment	76
6.17	Verification of carbonation depth of concrete tested in natural environments	77
6.18	Carbonation depth of concrete tested in accelerated environment (Authors' data)	77
6.19	Carbonation depth of concrete tested in accelerated environment (Sulpapha's data)	78
6.20	Verification of carbonation depth of concrete in accelerated environment	78
6.21	Prediction of carbonation depth of cement only concrete (Relative humidity = 75% and Temperature = 30 °C)	79
6.22	Prediction of carbonation depth of fly ash concrete (Relative humidity = 75% and Temperature = 30 °C)	79
6.23	Prediction of carbonation depth of cement only concrete (CO ₂ concentration = 650 ppm and Relative humidity = 75%)	80
6.24	Prediction of carbonation depth of fly ash concrete (CO ₂ concentration = 650 ppm and Relative humidity = 75%)	80
6.25	Test result of carbonation depth of mortar in accelerated environment (Effect of environmental temperature)	80

6.26	Prediction of carbonation depth of cement only concrete (CO ₂ concentration = 650 ppm and Temperature = 30 °C)	81
6.27	Prediction of carbonation depth of fly ash concrete (CO ₂ concentration = 650 ppm and Temperature = 30 °C)	81
6.28	Test result of carbonation depth of mortar in accelerated environment (Effect of relative humidity)	82
7.1	Relationship between slump and free water content of fresh concrete	84
7.2	Verification of slump of fly ash concrete	86
7.3	Verification of slump of concrete with various types of powder	86
7.4	Relationship between inverse of Vebe time and free water content	87
7.5	Verification of Vebe time (Ta Dan Dam)	88
7.6	Verification of Vebe time (Pak Moon Dam)	89