

List of Figures

Figure	Page
2.1 Some examples of natural handwriting of 46 classes of alphanumeric characters with their respective codes	6
2.2 Four samples of syllable	6
2.3 A sample of a complete sentence in natural handwriting	7
2.4 A demonstration of variable natural handwriting for the first consonant क	8
2.5 Two demonstrations of projection	14
2.6 Projection onto one-dimensional subspace	15
2.7 Projection onto vertical line and horizontal along with variance measurement	15
2.8 A perceptron	17
2.9 The decision surface represented by two-input perceptron	17
2.10 A sigmoid threshold unit	18
2.11 Two methods for fitting quadratic boundaries, quadratic decision boundaries (using LDA in five dimensional space; $x_1, x_2, x_1x_2, x_1^2, x_2^2$) on the left and quadratic decision boundaries (using QDA) on the right	20
2.12 Classification of query instance x_q in the sets of both positive and negative training examples by using different value of k	21
2.13 Feed-forward neural network with single hidden layer	23
2.14 Demonstration of Bayesian network with the help of chain rule for gathering knowledge of variables by using probability	24
2.15 Margin measurement for an optimal hyperplane	25
2.16 Measurement of absolute distance from an example x to boundary $g(x) = 0$	25
2.17 Use of slack variable in non-linearly separable case and its implication	26
2.18 Demonstration of non-linear mapping in case of low-dimensional space	27
2.19 A simple architecture of HMM	28
2.20 HMM topology for a character	29
2.21 A $(x_t, y_t / \theta_t)$ HMM architecture with pen direction feature (θ_t) and pen coordinate feature (x_t, y_t) at each self transition and inter-state transition respectively	29
2.22 A (x_t, y_t, θ_t) HMM architecture	29

2.23	A basic block diagram of a template-based on-line character recognition system	30
2.24	A sample of Jitter	33
2.25	Words with different orientations and skews	33
2.26	A sample of slope measurement along the pen trajectory	34
2.27	Feature design with the help of directional codes (Lee et al., 2000) (line segment approximation)	36
2.28	Feature design (Gao et al., 2000) with the help of standard strokes	36
2.29	Malik's proposed components of Urdu character	37
2.30	Sanparith's proposed elementary strokes for on-line handwriting. Elementary strokes are designed by 12 straight lines (es1 to es12), 12 convex strokes (es13 to es24) and 12 concave strokes (es25 to es36)	37
2.31	Zoning information from 8 different regions	38
2.32	Examples: (a) Euclidean, (b) City-Block and (c) Chess-Board distance measures	39
2.33	An example of warping path during the alignment of two non-linear sequences by using DTW	42
2.34	A sample of dendrogram providing an idea of agglomerative and divisive clustering algorithms	47
2.35	Types of agglomerative hierarchical clustering	48
2.36	Holdout Cross Validation	49
2.37	K-Fold Cross Validation	50
2.38	Leave-One-Out Cross Validation	50
3.1	A sample of complete specific stroke pre-processing	52
3.2	Feature selection	53
3.3	An example to determine the distance between two non-linear sequences using DTW technique	56
3.4	A graphical measurement of similarity/dissimilarity between the numerals pairs १ and २	57
3.5	A graphical agglomerative hierarchical clustering demonstration with significant cluster threshold by taking one of the numeral classes २	58
3.6	A graphical demonstration of grouping similar strokes from every character within a class क. Each encircled group in क-frame produces a representative stroke	59
3.7	Confusion pairs and their reasons of similarity	62
3.8	A rejected sample (क) due to very long descender	63

3.9	A sample of similar characters for humans to read	64
3.10	Three samples of characters having diminished descenders	66
3.11	Effect of pre-processing in correct recognition	69
3.12	Two rejected samples (भ and क) due to rewriting strokes	71
3.13	A complete comparison of four classifiers based on their accuracies	74
4.1	Four samples having multiple straight sequences	78
4.2	Threshold range ($St - Cs$) determination for shirorekha	79
4.3	Spatial relation between two strokes of the character क	80
4.4	A real example of how spatial relation is determined by taking a character क	80
4.5	Grouping of characters of a specific class अ based on the number of strokes used	81
4.6	Clustering technique for two-stroke अ	82
4.7	Template management for a class of character अ having many groups	82
4.8	Correct recognition of confusion character म (भ) by handling spatial information of the strokes	83
4.9	Confusion between य ↔ च	83
4.10	Two confusions pairs: द → ढ	85
4.11	Two confusions pairs: स → ग	85
4.12	Misclassified example: न → म	86
4.13	Misclassified example: ल → त, which are looking different in printed format	88
4.14	Confusion of झ with स even though a lot of dissimilar feature in between them in printed format (झ → स)	88
A.1	Both full and half Consonants	101
A.2	A Few samples of Conjunct Consonants	102
A.3	Vowels	102
A.4	Numerals	102
A.5	Sample of Vowels, as a modifier for consonant	102
A.6	A few samples of words formation	102
A.7	A few samples of complete sentences	102
B.1	Natural Writings	105
C.1	Input Window	107

C.2	Discrete Warping Path	115
C.3	Distance Matrix	115
C.4	Clustering Results - Method: 'Single' and $k=4$	116
C.5	A sample of a stroke	117



สำนักหอสมุด