

LIST OF TABLES

TABLE	PAGE
4.1 Parameters used for simulation of A_{g1} according to the KT model	30
4.2 Parameters used for simulation of A_{g2} according to the KT model	30
4.3 Parameters in Duffing (hardening-type) system	31
4.4 Parameters used in Clough-Johnston hysteretic model ($\alpha = 0.3$)	38
4.5 Parameters used in Clough-Johnston hysteretic model ($\alpha = 0.1$)	47
4.6 Parameters used in EBWBN hysteretic model ($\alpha = 0.3$)	53
4.7 Parameters used in EBWBN hysteretic model ($\alpha = 0.1$)	58
A Generated seismic record, A_{g1} , using Kanai-Tajimi model 1600 data points at equal spacing of 0.01sec (read column by column from left to right) The unit is g	A-2
B Generated seismic record, A_{g2} , using Kanai-Tajimi model 1800 data points at equal spacing of 0.01sec (read column by column from left to right) The unit is g	B-2
C Scaled El-Centro 1940 North-South component, A_{g3} , 3119 data points at equal spacing of 0.01sec (read column by column from left to right) The unit is g	C-2
D The optimal weight for SDOF duffing (hardening type) system	D-2
E The optimal weight for SDOF Clough-Johnston hysteretic system ($\alpha = 0.3$) with known damping	E-2
F The optimal weight for SDOF Clough-Johnston hysteretic system ($\alpha = 0.3$) with unknown damping	F-2
G The optimal weight for SDOF Clough-Johnston hysteretic system ($\alpha = 0.1$) with unknown damping	G-2
H The optimal weight for SDOF Extened-Bouc-Wen-Barber-Noori hysteretic system ($\alpha = 0.3$) with unknown damping	H-2
I The optimal weight for SDOF Extened-Bouc-Wen-Barber-Noori hysteretic system ($\alpha = 0.1$) with unknown damping	I-2
J The optimal weight for MDOF duffing (hardening type) system with unknown damping	J-2