

## LIST OF FIGURES

FIGURE	PAGE
1.1 High-rise buildings and wind measurement tools	2
2.1 Equivalent static pressure (NBC code)	17
2.2 Procedure to determine reference wind speed	18
2.3 Thailand map of reference mean wind speed in one hour at height of 10 m in an open exposure for 50 years returned period	19
2.4 Exposure factor as a function of terrain roughness and height above ground	20
2.5 Peak factor as a function of average fluctuation rate	20
2.6 Size reduction factor as a function of width, height and reduced frequency of structure	21
2.7 Gust energy ratio as a function of wave number	21
2.8 Background turbulence factor as a function of width and height of structure	22
2.9 Principle of applying vibration control on high-rise building	23
3.1 Mathematical model of a first mode structure attached with TMD	33
3.2 Complex frequency response of 400-m high building with and without TMD	33
3.3 Mathematical model of first mode structure attached with MTMD	34
3.4 Frequency distribution of MTMD around structural natural frequency	34
3.5 Robustness of TMD and MTMD on natural frequency error ( $\gamma_0$ ) for 400 m high-rise building	35
3.6 Robustness of TMD and MTMD on total critical damping ratio error of dynamic damper	35
3.7 Effectiveness and robustness of MTMD for 400 m high-rise building	36
3.8 Harmonic frequency response of 400-m building with a number of MTMDs with different natural frequency distribution	36
3.9 Complex frequency response of 400-m building with a number of MTMDs with different damping ratio	37
4.1 Geometric of tuned liquid damper	42
4.2 Complex frequency response of 183-m high building with optimal TMD and optimal rectangular TLD	42
4.3 Design planning of TLD by EXCEL computer program	43
4.4 Mathematical model of first mode structure with MTLT	44
4.5 Robustness of TLD and MTLT on natural frequency for 400 m high-rise building (along wind direction)	44
5.1 Mathematical model of first mode structure attached with ATMD	50
5.2 Close loop active damper control	50
6.1 Building examples	58
6.2 Equivalent static pressure for 183-m high building (Exposure B)	59
6.3 Equivalent static pressure for 317.5-m high building (Exposure B)	59
6.4 Equivalent static pressure for 400-m high building (Exposure C)	60
6.5 Effect of mass ratio on maximum roof displacement in along-wind directions of three high-rise building in exposure A	61
6.6 Effect of mass ratio on maximum roof displacement in across-wind directions of three high-rise building in exposure A	61

<b>FIGURE</b>	<b>PAGE</b>
6.7 Effect of mass ratio on peak stroke of TMD in along-wind directions of three high-rise building in exposure A	62
6.8 Effect of mass ratio on peak stroke of TMD in across-wind directions of three high-rise building in exposure A	62
6.9 Equivalent static pressure for 183-m high building (Exposure B)	63
6.10 Equivalent static pressure for 317.5-m high building (Exposure B)	63
6.11 Equivalent static pressure for 400-m high building (Exposure C)	64
6.12 Varying the acceleration gain (be mean of active force) of ATMD	65
6.13 Effect of acceleration feedback gain coefficient on equivalent damping ratio of 400 m high building with ATMD for four mass ratios	66
6.14 Effect of acceleration feedback gain coefficient on peak roof displacement of 400 m high building with ATMD for four mass ratios in along wind direction in exposure A	66
6.15 Effect of acceleration feedback gain coefficient on peak stroke of ATMD of 400 m high building for four mass ratios in along wind direction in exposure A	67
6.16 Effect of acceleration feedback gain coefficient on peak active force of ATMD of 400 m high building for four mass ratios in along wind direction in exposure A	67
6.17 Effect of acceleration feedback gain coefficient on peak roof displacement of 400 m high building with ATMD for four mass ratios in across wind direction in exposure A	68
6.18 Effect of acceleration feedback gain coefficient on peak stroke of ATMD of 400 m high building for four mass ratios in across wind direction in exposure A	68
6.19 Effect of acceleration feedback gain coefficient on peak active force of ATMD of 400 m high building for four mass ratios in across wind direction in exposure A	69