

List of Figures

Figure	Caption	Page
1.1	Typical vapour compression and ejector refrigeration cycle.	2
2.1	Configurations of typical ejectors.	7
2.2	Variation of stream pressure and velocity as a function of location along a steam ejector [31].	9
2.3	An example of Schlieren photograph of flow in an air ejector (Source: Matsuo et al. [32]).	10
2.4	Static pressure distribution along duct centerline and wall surface in constant-area duct [33].	11
2.5	Performance characteristics of a steam ejector based on experimental data provided by Eames and Aphornratana [2].	13
2.6	Effect of operating pressures on performance of a steam jet refrigerator based on experimental data provided by Eames and Aphornratana [2].	14
3.1	The experimental R141b ejector refrigerator.	20
3.2	The immersible electric heater.	21
3.3	Connection of the ejector in the experimental refrigerator.	22
3.4	The pumping system with the subcooler.	24
3.5	Schematic diagram of the experimental R141b ejector.	27
3.6	Photograph of an ejector used in the experiment.	28
3.7	Photograph of the primary nozzle.	28
4.1	Flow chart of the CFD procedure for modeling the R141b ejector.	35
4.2	Geometry setup for the R141b ejector.	37
4.3	Calculation domain and grid structure of the R141b ejector CFD model.	39
4.4	Static pressure profiles for different wall treatment assumptions for a steam ejector (manipulated from data provided by Chunnanond [47]).	42
5.1	Comparison between CFD and experimental results of the primary mass flow rate.	48
5.2	Static pressure profile along the ejector at $T_P = 100^\circ\text{C}$, $T_S = 5^\circ\text{C}$ and at various condenser pressures, effect of downstream pressure.	50
5.3	Static pressure profile along the ejector at $T_C = 30^\circ\text{C}$ ($P_C = 0.94$ bar), effect of primary and secondary fluid pressure.	50
5.4	Static pressure profile along the ejector at $T_P = 110^\circ\text{C}$, $T_S = 5^\circ\text{C}$, and $P_C = 0.94$ bar, effect of the primary nozzle throat diameter.	51
5.5	Static pressure profile along the ejector at $T_P = 100^\circ\text{C}$, $T_S = 5^\circ\text{C}$, and $P_C = 0.94$ bar, effect of the mixing chamber inlet diameter.	51
5.6	Static pressure profile along the ejector at $T_P = 100^\circ\text{C}$, $T_S = 5^\circ\text{C}$, and $P_C = 0.94$ bar, effect of the throat length.	52
5.7	Validation of static pressure profile along the ejector at $T_P = 100^\circ\text{C}$, $T_S = 5^\circ\text{C}$, and $P_C = 0.94$ bar, effect of the nozzle exit position (NXP).	52
5.8	Validation of entrainment ratio, effect of operating conditions.	53
5.9	Validation of entrainment ratio, effect of primary nozzle throat diameter.	54

List of Figures (Cont')

Figure	Caption	Page
5.10	Validation of entrainment ratio, effect of mixing chamber inlet diameter.	54
5.11	Validation of entrainment ratio, effect of throat length.	55
5.12	Validation of entrainment ratio, effect of nozzle exit position.	55
5.13	Comparison between the CFD and the experimental results of the entrainment ratio in the choked flow and the unchoked flow region for various operating conditions and geometries (case 1 to case 11 correspond to the experimental cases in Table B.1).	56
5.14	Comparison between the CFD and the experimental results of the critical back pressure for various operating conditions and geometries (case 1 to case 11 correspond to the experimental cases in Table B.1).	58
6.1	Filled contours of Mach number and static pressure distribution of the R141b ejector.	62
6.2	Primary flow states of the flow in the ejector colored by contours of Mach number.	63
6.3	Mach number and static pressure distribution in the steam ejector based on the work of Sriveerakul et al. [39 and 40].	67
7.1	Performance characteristics of an R141b ejector, effect of operating conditions.	73
7.2	Effect of downstream operating conditions on the flow in the R141b ejector	74
7.3	Path lines colored by Mach number of the flow in R141b ejector	75
7.4	Effect of upstream operating conditions on the flow in the R141b ejector.	78
7.5	Simulated Entrainment ratio and mass flow rates of the two streams at different upstream pressure ratio.	80
8.1	Performance characteristics of the R141b ejector, effect of primary nozzle throat diameter.	86
8.2	Effect of the primary nozzle throat diameter on the flow in the R141b ejector.	87
8.3	Performance characteristics of the R141b ejector, effect of mixing chamber inlet diameter.	89
8.4	Effect of the mixing chamber inlet diameter on the flow in the R141b ejector.	90
8.5	Performance characteristics of the R141b ejector, effect of throat length.	91
8.6	Effect of the throat length on the flow in the R141b ejector.	92
8.7	Performance characteristics of the R141b ejector, effect of nozzle exit position.	95
8.8	Effect of the nozzle exit position (NXP) on the flow in the R141b ejector.	96