

## List of Figures

Figure		Page
1.1	Low resolution and relatively noisy image ( $640 \times 488$ ) captured inexpensive IEEE1394 web cam. By looking at zoomed hand, it is obvious that detecting hands in this image is very challenging.	2
3.1	Hand detection system architecture. Scanned image pages are classified as hand or non-hand by a cascade based on Haar-like features then further filtered by a post-processor based on skin pixel blob analysis.	7
3.2	Explanation of how the scanning window extracts image patches from the image.	8
3.3	Classifiers in cascade arrangement speeds up the classification by rejecting most non-hand image patches	8
3.4	Haar-like features used to construct weak classifiers in the boosted classifier cascade. (a) Viola and Jones features. (b) Lienhart and Maydt features.	9
3.5	Gentle AdaBoost algorithm used to train the classifier cascade of my hand detector system.	10
3.6	Cascading algorithm arranges boosted classifiers in cascade order to improve detection speed.	11
3.7	(a) Ideal skin detected image of proper hand, which may be produced by skin detector. (b) Largest connected skin blob of image (a), on which holes are filled. (Images are synthesized to model problem.)	13
3.8	Illustration to demonstrate how useful four features are in the discrimination between image patches contain hand and those do not contain proper hand. Here, feature values for each image are absolute values, i.e. they are not normalized. (Images are synthesized to model problem.)	14
4.1	Example images from three video sequences taken while person is walking. The walking path of the model is parallel to the direction of camera and it is perpendicular to camera's focal axis in sequence 2. In sequence 3, model is walking diagonally across the field.	19
4.2	Example positive training images scaled to $24 \times 24$ for better visualization.	20
4.3	Example images used for skin detector training. (a) Original color image. (b) Binary mask image, in which white pixels represent skin pixels and black pixels represent non-skin pixels on the image (a).	21

4.4	ROC curve between true positive and false positive for different threshold on Mahalanobis distance. True positive and false positive rate are calculated based on number of true detection and false detection input to the Mahalanobis Classifier.	23
5.1	Hands detected by our complete hand detector system. All detections are scaled down to standard size 24x24 pixels for easy visualization.	25
5.2	Example detection results of our proposed hand detector system on six consecutive frames from test image sequence. Detection on right hand in image 2 is considered as false detection because of the relatively huge detection window size.	27
5.3	Bar graph showing the reduction of false positives at each important stage of the hand detector system.	28
5.4	Both image patch 1 and 2 are classified as hand by the boosted classifier cascade. Skin detected images of those two images are shown below each of the images. Boundary feature extracted from skin detected binary image helps in elimination of this kind of false detection.	29